



INTRODUCING

OUR NEW HIGH FLOW FERTILIZER AND CHEMICAL PUMP



PUMP:

- Pump is constructed of Dupont[®] Rynite Glass-Filled Polyester for maximum corrosion and chemical resistance.
- EPDM Elastomers
- Hardened Siliconized Graphite Shaft Seal faces offer durability and extended service life.
- All fasteners are Stainless Steel
- 3" Port size with maximum flow rate of 400 GPM
- Self-priming with vertical suction lift to 25 feet.

ENGINE:

- LCT's patented commercial series engine designed to deliver maximum performance for the most rugged conditions with industrial grade components and uniquely designed features.
- Engine features LCT CMXX Commercial duty warranty of 1 year.
- Features Include Overhead Valve Design, Cast Iron Sleeve Bore, Dual Ball Bearings, Rugged Metal Fuel Tank, Low Noise Muffler, Forged Crankshaft and Low Oil Alert System.
- Lubrication System is engineered to deliver extra lubrication to the internal bearings reducing heat build up and extending engine run life.
- Electric Start and Roll Cage are standard.
- Mounted on a heavy duty roll cage with rubber feet for vibration absorption. Features a welded carry frame for easy handling.

MODEL:

MODEL	ENGINE	PORT	MAX FLOW	MAX TDH	WT.
TE3TEP E420CC	420cc LCT CMXX W/Electric Start	3"	400 GPM	87' (38psi)	115 lbs.



Division of ASM Industries, Inc.

41 Industrial Circle
Lancaster PA 17601
email: sales@pacerpumps.com
www.pacerpumps.com

Phone: 717-925-8240
Toll Free: 800-233-3861
FAX: 717-925-8242

